Props, Fans, & Pumps

Design & Performance

...just the color figures for those who got the B&W printed book...

by D. James Benton

Copyright © 2020 by D. James Benton, all rights reserved.

Forward

Propellers, fans, and pumps are an integral part of many machines of industry, transportation, and modern living. The designs are as diverse as the applications, but the theory behind how these devices work is the same. In this text we will consider nuances of design, such a prop cupping, trailing edge truncation, and blade curling. We will derive and apply the formulas in order to design and evaluate the performance of these fascinating devices. All of the software described herein is available free online.


All of the examples contained in this book,
(as well as a lot of free programs) are available at...
http://www.dudleybenton.altervista.org/software/index.html














































































1 2					E	F	G	H	1200 1000	J	K	L	M
2		2°pitch		6°pitch		10°pitch		14°pitch		18"	oitch	22°ptch	
	KCFM	Es	Et	Es	Et	Es	Et	Es	Et	Es	Et	Es	Et
3	500	69.0%	74.5%	66.4%	69.9%	62.9%	65.4%	48.5%	50.3%	37.0%	38.3%	29.4%	30.4%
4	600	4								,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,			
5	700	6 80% T				T	_						7 6
6	800	3										2°pitch	6
7	840	70%				/•\						6*pitch	6
8	900					1	14					10°pitch	
9	1000				1	(J.	Mary	13.00			1		I 6:
10	1070	60%			1		11	-	-		1	14°pitch	P 2
11	1100	-			W	1	11	1\.	1	- I		18°pitch	6
12	1200	. } <u>}</u> }	0% 🕂	-	-/-	/	1	-		*		22°pitch	6
-	1300	- E			11/	1 /	1 /	\cap \		1	/		1 6
100000	1310	ી દે 4	o% ∔			-		,	1	-			1 6
15	1400	Static Efficiency		-L	///	V /	1L	۱I.	\ L	/ V			6
16		1 8		- /8	V /	1 1	П	M	* I	7.1	\		L
17		್ಷರ್	0% 🕂	1//		/		1	1	\forall			1 H
18				-// A	//		- 11	₩	M	M	\		L
19		2	10% 🕂	##			++-		+	—₩	_	_	1 H
20				11/1//			11	- /\	- 1	- A	- \	\ \	LΗ
21		1	0%	444			\perp				\		4 H
22		- '	· /				11	- 1 \	1		\ \	1	
23		-	0% 🖊	·			1]	- 1.1	- 11		\		V H
24		-		0.54		00	750	4000	4050	4500	47	50 0	- H
25			0	250	J 5	00	750 Elor	1000 w [KCFI	1250	1500	179	50 2	000
26		_					rio	w [wcri	**1				




































































































Figure 83. Horizontal Shaft Pump

